

NOTE:

1. THICKNESS OF A.B. AND A.C. TO BE DETERMINED BY SOIL TEST AT TIME OF GRADING OPERATIONS.
2. MINIMUM PAVING THICKNESS PER SPECIFICATIONS SECTION 8.07 OF THIS ORDINANCE.
3. SEE STANDARD NO. 212 FOR A.C. DIKE DETAIL.
- *4. CONCRETE CURB, GUTTER, AND SIDEWALK MAY BE REQUIRED AS DETERMINED BY THE DIRECTOR OF TRANSPORTATION.


NOT TO SCALE

- A.B. = AGGREGATE BASE
- A.C. = ASPHALT CONCRETE
- EP = EDGE OF PAVEMENT
- ES = EDGE OF SHOULDER
- ETW = EDGE OF TRAVELED WAY
- FL = FLOW LINE
- O.G. = ORIGINAL GROUND
- RW = RIGHT OF WAY

APPROVED BY:

George A. Johnson
 DIRECTOR OF TRANSPORTATION
 GEORGE A. JOHNSON, RCE 42328

DATE: 05/01/07



COUNTY OF RIVERSIDE

**MOUNTAIN ARTERIAL
 HIGHWAY
 (110' R/W)**

STANDARD NO. 95

REVISIONS	REV.	BY:	APR'D	DATE	REV.	BY:	APR'D	DATE
	1				4			
	2				5			
	3				6			